



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

## View LED Pendant VIP Series

### Features

Frosted glass cylinder inside a clear glass cylinder suspended with a 9 ft. cord. Can be ordered individual or with a multi-point canopy. Mounts to a standard junction box (not included).

### Construction

The outer glass cylinder is 16" tall and 4-5/8" in diameter and the inner glass cylinder is 14" tall and 3-7/8" in diameter. The unit is held into place by three decorative studs. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

### Finish

The canopy is plated in Satin Nickel.

### Diffuser

Inner glass cylinder is 0.14" thick. Colors include cream (CR) and white (WH). Clear outer glass.

### Electrical

#### D1 Driver

Direct wired with a constant current low voltage electronic LED driver rated at 120 VAC. The driver is dimmable with a 2-wire (Triac) or electronic low voltage (ELV) dimmer switch.

#### D2 Driver

Direct wired with a constant current low voltage electronic LED driver rated for 120-277 VAC. LED driver is dimmable 0-10V DC.

### Lamping

All pendants include a 10W LED module. Light engine produces 1000 source lumens. 3000K and 4000K (CCT). 50,000 hr. LED life, 90 CRI.

### Certification

All fixtures are ETL listed for damp locations.

### Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

### Specifications and dimensions

subject to change without notice.



White

Cream



## Ordering Information:

4-5/8" DIA. x 16" H

Series	Source Lumens	LED	CCT	Driver	Finish	Glass	Canopy Options
VIP	1000	L	30 3000K 40 4000K	D1 Voltage (120V TRIAC Dimming) D2 Voltage (120-277V 0-10V Dimming)	SN Satin Nickel	CR Cream WH White	Blank Monopoint LNR3 (3) Light Linear RND3 (3) Light Round RND6 (6) Light Round

Example: VIP1000L30D1SNCRNRND6