

Ion LED Sconce IONS Series

Features

Layered modern forms in multi-dimensional metal housing. Indirect light for wall wash effect. For use in hallways, corridors, or anywhere general lighting is needed. Vertical or horizontal mounting. Requires a rectangular 2 in x 4 in. handy box for installation (not included).

Construction

Back plate is die-formed of 22-gauge steel. Standard mounting holes and hardware are included. Power supply connections must be made inside a handy box (not included).

Finish

Satin nickel.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277 VAC, 60 Hz LED. LED driver is 0-10V DC dimmable.

LED

Integrated LED modules capable of producing: 18W = 1500 source lumens 3000K (CCT) rated for 50,000 hrs., 90 CRI

Certification

All fixtures are cETLus listed for damp locations. ADA


Warranty

Limited warranty. This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.

LOCATION	DATE
PREPARED	
BY	QUANTITY
COMMENTS	
	FIXTURE TYPE
CATALOG NUMBER	
	•





Ordering Information:

		Source				
Satin Nickel	LED	Lumens	CCT	Н	W	D
IONS032015L 30D2SN	18\//	1500	3000K	20"	3-1/4"	2-1/2"