

Benton LED Outdoor Sconce BNTW Series

Features

Ideal use for general lighting in or outdoor residential, commercial, and hospitality applications. Fixture can be mounted to a standard junction box (not included).

Construction

Polycarbonate housing and painted in weather resistant powder coating. Power supply connections must be made inside a junction box (not included).

Finish

Black, Textured Grey or Oil-Rubbed Bronze finish.

Diffuser

Frosted polycarbonate diffuser.

Electrical

Input 120 VAC / 60Hz.

Minimum starting temp -4° F/-20° C
Integrated photocell for dusk to dawn operation.

LED

Integrated LED modules capable of producing: 9W = 800 delivered lumens
Adjustable Choice 3000K, 4000K, 5000K (CCT).
Rated for 50,000 Hrs. 80 CRI.


Certification

All fixtures are cETLus listed for outdoor wet locations. Title 24/JA8 Compliant Ideal for coastal applications (IP65)

Warranty

5 Year Limited Warranty: Restrictions apply based on location.

Specifications and dimensions subject to change without notice.
















Ordering Information:

				Delivered				
Black	Textured Grey	Oil-Rubbed Bronze	LED	Lumens	Adjustable CCT	Н	W	D
BNTW0505LAJENBK	BNTW0505LAJENTG	BNTW0505LAJENBZ	9W	800	3000K/4000K/5000K	5"	5"	6-1/4"