

Dexter LED Outdoor Sconce DEXW Series

LOCATION PREPARED BY COMMENTS CATALOG NUMBER DATE QUANTITY FIXTURE TYPE







Features

This outdoor LED light is ideal for security and general lighting.

Up illumination (1-Light) or Up/down-light illumination (2-Light) with adjustable beam angle for outdoor or indoor residential, commercial, and hospitality applications.

Vertical or horizontal mounting. Fixture mounts to a standard junction box (not included).

Construction

Fabricated aluminum construction. Standard mounting holes and hardware are included. Power supply connections must be made inside a junction box (not included).

Finish

Black, Bronze or White powder coat finish.

Diffuser

Clear glass diffuser.

Electrical

Input 120-277 VAC / 60 Hz. Minimum starting temp -4° F/ -20°C.

LED

Integrated LED modules capable of producing: 1-LIGHT - 12W = 1200 source lumens, 537 delivered lumens 2-LIGHT - 24W = 2400 source lumens, 1025 delivered lumens 3000K (CCT). Rated for 50,000 Hrs., 80 CRI.

Certification

All fixtures are cETLus listed for wet locations. Title 24/JA8 Compliant (outdoor only).

Warranty


Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase.

Specifications and dimensions subject to change without notice.









Ordering Information:

				Source	Delivered				
Black	Bronze	White	LED	Lumens	Lumens	CCT	Н	W	D
DEXW060612L30MVBK (1-LIGHT)	DEXW060612L30MVBZ (1-LIGHT)	DEXW060612L30MVWH (1-LIGHT)	12W	1200	537	3000K	5-1/2"	5-1/2"	2-1/4"
DEXW060624L30MVBK (2-LIGHT)	DEXW060624L30MVBZ (2-LIGHT)	DEXW060624L30MVWH (2-LIGHT)	24W	2400	1025	3000K	5-1/2"	5-1/2"	2-1/4"