

Ideal LED Contemporary Oval PIDF Series

Features

Contemporary framed oval ceiling mount with a metal trim band. Ideal use in kitchens, hallways, and anywhere general lighting is needed. Provides lighting in residential, commercial and hospitality applications. Fixture mounts to standard junction box (not included).

Construction

Housing is die-formed of 22-gauge steel. Standard mounting holes and hardware included. The canopy fits over a standard junction box. Power supply connections must be made inside a junction box (not included).

Finish

Housing is finished in lighting grade white baked gloss enamel paint. Trim ring is Satin Nickel finish.

Diffuser

Diffuser is .080" thick vaccum formed smooth white acrylic.

Electrical

Input 120-277 VAC, 60 HZ LED. Not compatible with dimmers.

Lamping

Integrated LED modules capable of producing: 32W = 3700 source lumens 4000K (CCT) rated for 50,000 hrs., 80 CRI.

Certification

ENERGY STAR® qualified
All fixtures are cETLus listed for indoor damp locations.

Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date of purchase

Specifications and dimensions subject to change without notice.

Ordering Information:

Satin Nickel	LED	Source Lumens	ССТ	L	W	D
PIDF172900L40MVSN	32W	3700	4000K	32"	17"	4"

LOCATION	DATE
PREPARED BY	QUANTITY
COMMENTS	FIXTURE TYPE
CATALOG NUMBER	





