



LOCATION		DATE
PREPARED BY		QUANTITY
COMMENTS		FIXTURE TYPE
CATALOG NUMBER		

August LED Outdoor Sconce AUGW Series

Features

Ideal use for general lighting in indoor or outdoor residential, commercial, and hospitality applications.
Fixture can be mounted to a standard junction box (not included).

Construction

Stainless steel housing with aluminum die-cast trim and painted in weather resistant powder coating. Back pan is made from 12 gauge stamped aluminum material with matching powder coat finish. Power supply connections must be made inside a junction box (not included).

Finish

Black or Painted Nickel finish.

Diffuser

White acrylic diffuser.

Electrical

Input 120-277VAC / 60Hz.
Minimum starting temp -4° F/-20° C

LED

Integrated LED modules capable of producing:
26W = 1700 delivered lumens
35W = 2200 delivered lumens
40W = 2600 delivered lumens
Adjustable Choice 3000K, 3500K, 4000K (CCT).
Rated for 50,000 Hrs. 80 CRI.

Certification

All fixtures are cETLus listed for outdoor wet locations.
Title 24/J8A Compliant
ADA

Option

Integrated Dusk to Dawn photocell (-PC)

Warranty

5 Year Limited Warranty:

Restrictions apply based on location.

**Specifications and dimensions
subject to change without notice.**

Ordering Information:

		LED	Delivered Lumens	Adjustable CCT	H	W	D
Black	Painted Nickel						
AUGW0612LAJMV BK	AUGW0612LAJMV NP	26W	1700	3000K/3500K/4000K	12"	5-1/2"	3-3/4"
AUGW0612LAJMV BK-PC	AUGW0612LAJMV NP-PC	26W	1700	3000K/3500K/4000K	12"	5-1/2"	3-3/4"
AUGW0720LAJMV BK	AUGW0720LAJMV NP	35W	2200	3000K/3500K/4000K	20"	7"	3-3/4"
AUGW0720LAJMV BK-PC	AUGW0720LAJMV NP-PC	35W	2200	3000K/3500K/4000K	20"	7"	3-3/4"
AUGW0736LAJMV BK	AUGW0736LAJMV NP	40W	2600	3000K/3500K/4000K	36"	8"	3-3/4"
AUGW0736LAJMV BK-PC	AUGW0736LAJMV NP-PC	40W	2600	3000K/3500K/4000K	36"	8"	3-3/4"

